



# Ultimaker 2+ Connect Air Manager

## Product data sheet

Upgrade your peace of mind

The Ultimaker 2+Connect Air Manager <sup>1</sup> gives you more confidence and setup flexibility. Designed to increase user safety, it removes up to 95% of ultrafine particles (UFPs) while top and front enclosures shield users from hot and moving components.

Key features

- ✓ EPA filter :Removes up to 95% of UFPs
- ✓ Enhanced safety :Encloses the top and front of the printer
- ✓ Easy setup :Printer detects when the Air Manager is connected

### Ultimaker 2+Connect Air Manager specifications

Properties	Filter technology	EPA filter
	Fan technology	Air extraction by low-noise brushless fan
	Filter efficiency	Up to 95%
	Filter replacement	Recommended every 1,500 print hours (approx.1 year)
	Operating sound	<51 dBA (including printer)
	Connection (data and power)	UMB connection (included)
	Compatible materials	Optimized for Ultimaker PLA, ToughPLA, ABS, Nylon, CPE, CPE+, PC, PP,TPU 95A (Also supports third-party materials)
	Physical dimensions	Dimensions (XYZ)
Dimensions (including printer)		342 x 460 x 636 mm (13.5 x 18.1 x 25 in)
Shipping box dimensions		491 x 401 x 380 mm (19.3 x 15.7 x 15 in)
Net weight		2.65 kg (5.8 lbs)
Warranty		Warranty period

<sup>1</sup> Requires Ultimaker 2+Connect 3D printer. For illustrative purposes, the Air Manager is shown with the printer



FM 686003 EMS 692523